

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

SECTION 1: Identification

1.1 Product identifier

Trade name	DRYLOK Extreme Basement & Masonry Waterproofing (White)
Alternative number(s)	28612; UFI: FS2M-G7N1-X80J-9QNP 28613; UFI: KCCM-37NR-K801-FUX4 28615; UFI: 3HWM-A7Q4-U801-R4G1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Waterproofing sealers Concrete masonry paint, coating and lacquer paint related material
--------------------------	---

1.3 Details of the supplier of the safety data sheet

United Gilsonite Laboratories, Inc.
1396 Jefferson Avenue
Dunmore PA 18509
United States

Telephone: +1 (570) 344-1202
Telefax: (570) 969-7634
e-mail: sales@ugl.com
Website: <http://www.ugl.com/>

e-mail (competent person)	nicholas.shaffmaster@ugl.com (Nicholas Shaffmaster)
---------------------------	---

1.4 Emergency telephone number

Emergency information service	1-800-424-9300 Chemtrec (NORTH AMERICA) Emergency telephone number: outside office hours
-------------------------------	---

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.7	reproductive toxicity	1B	Repr. 1B	H360D

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

- Pictograms

GHS07, GHS08



- Hazard statements

H317 May cause an allergic skin reaction.
H340 May cause genetic defects.
H350 May cause cancer.
H360D May damage the unborn child.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P201 Obtain special instructions before use.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 If on skin: Wash with plenty of water.
P308+P313 If exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P405 Store locked up.
P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Quartz (SiO₂), 2-methylpropane, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate), Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one

2.3 Other hazards

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Titanium dioxide	CAS No 13463-67-7	5 - < 10	Carc. 2 / H351
Diethylene glycol monomethyl ether (DM)	CAS No 111-77-3	1 - < 5	Repr. 2 / H361d
Aluminium oxide	CAS No 1344-28-1	0.05 - < 1	Acute Tox. 3 / H331
Quartz (SiO ₂)	CAS No 14808-60-7	0.05 - < 1	Carc. 1A / H350

DRYLOK Extreme Basement & Masonry Waterproofer (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

Name of substance	Identifier	Wt%	Classification acc. to GHS
2-methylpropane	CAS No 75-28-5	0.05 - < 1	Muta. 1B / H340 Carc. 1A / H350 Flam. Gas 1 / H220 Press. Gas C / H280
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	CAS No 13463-41-7	0.05 - < 1	Acute Tox. 4 / H302 Acute Tox. 2 / H330 Eye Dam. 1 / H318 Repr. 1B / H360D STOT RE 1 / H372
1,2-benzisothiazol-3(2H)-one	CAS No 2634-33-5	< 0.05	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS No 55965-84-9	< 0.05	Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 4 / H332 Skin Corr. 1C / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

DRYLOK Extreme Basement & Masonry Waterproofer (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

DRYLOK Extreme Basement & Masonry Waterproofers (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as

frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	alpha-Alumina	1344-28-1	REL							appx-D	NIOSH REL
US	alpha-alumina	1344-28-1	PEL		15					i, dust	29 CFR 1910.1000
US	alpha-alumina	1344-28-1	PEL		5					r, dust	29 CFR 1910.1000
US	aluminium, insoluble compounds	1344-28-1	TLV®		1					r	ACGIH® 2022
US	aluminium oxide	1344-28-1	PEL (CA)		10					dust	Cal/ OSHA PEL
US	aluminium oxide	1344-28-1	PEL (CA)		5					r	Cal/ OSHA PEL
US	titanium dioxide	13463-67-7	PEL		15					i, dust	29 CFR 1910.1000
US	titanium dioxide	13463-67-7	REL							lowest, appx-A	NIOSH REL

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	Titanium dioxide finescale particles	13463-67-7	TLV®		2.5					r	ACGIH® 2022
US	Titanium dioxide nanoscale particles	13463-67-7	TLV®		0.2					r	ACGIH® 2022
US	Calcium silicate, naturally occurring as Wollastonite	13983-17-0	TLV®		1					i, noAsb_less1Sil	ACGIH® 2022
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx-A	NIOSH REL
US	isobutane	75-28-5	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	isobutane	75-28-5	TLV®			1,000				E	ACGIH® 2022

Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
appx-D	see Appendix D - Substances with No Established RELS
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
E	explosive
i	inhalable fraction
lowest	exposure by all routes should be carefully controlled to levels as low as possible
noAsb_less1Sil	contains no asbestos and less than 1% free crystalline silica
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

DRYLOK Extreme Basement & Masonry Waterproofer (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	white
Particle	not relevant (liquid)
Odor	like ammonia

Other safety parameters

pH (value)	9 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	193 °C at 760 mmHg
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	20.4 vol%
Vapor pressure	1 mmHg at 64.3 °C
Density	1.213 g/cm ³ at 20 °C
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

DRYLOK Extreme Basement & Masonry Waterproofer (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

Auto-ignition temperature	194 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Aluminium oxide	1344-28-1	inhalation: vapor	3 mg/l/4h
Aluminium oxide	1344-28-1	inhalation: dust/mist	>0.888 mg/l/4h
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	13463-41-7	oral	302 mg/kg
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	13463-41-7	inhalation: dust/mist	0.05 mg/l/4h
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	670 mg/kg

DRYLOK Extreme Basement & Masonry Waterproofer (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	oral	457 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	dermal	660 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	inhalation: vapor	11 mg/l/4h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	inhalation: dust/mist	2.36 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
Quartz (SiO ₂)	14808-60-7	1	
Titanium dioxide	13463-67-7	2B	

Legend

1 Carcinogenic to humans
2B Possibly carcinogenic to humans

Reproductive toxicity

May damage the unborn child.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Diethylene glycol mono-methyl ether (DM)	111-77-3	LC50	5,741 mg/l	fish	96 h
Diethylene glycol mono-methyl ether (DM)	111-77-3	EC50	1,192 mg/l	aquatic invertebrates	48 h
2-methylpropane	75-28-5	LC50	49.9 mg/l	fish	96 h
2-methylpropane	75-28-5	EC50	19.37 mg/l	algae	96 h
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	13463-41-7	LC50	2.6 µg/l	fish	96 h
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	13463-41-7	EC50	8.2 µg/l	aquatic invertebrates	48 h
1,2-benzisothiazol-3(2H)-one	2634-33-5	LC50	16.7 mg/l	fish	96 h
1,2-benzisothiazol-3(2H)-one	2634-33-5	EC50	2.94 mg/l	aquatic invertebrates	48 h
1,2-benzisothiazol-3(2H)-one	2634-33-5	ErC50	150 µg/l	algae	72 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	LC50	0.19 mg/l	fish	96 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	EC50	0.16 mg/l	aquatic invertebrates	48 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	ErC50	19.9 µg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Diethylene glycol mono-methyl ether (DM)	111-77-3	EC50	>1,000 mg/l	microorganisms	30 min

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	13463-41-7	EC50	29 µg/l	aquatic invertebrates	21 d
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	13463-41-7	ErC50	4.1 µg/l	algae	120 h
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	13463-41-7	EbC50	3 µg/l	algae	120 h
1,2-benzisothiazol-3(2H)-one	2634-33-5	EC50	13 mg/l	microorganisms	3 h
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	LC50	0.07 mg/l	fish	14 d
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	EC50	>0.18 mg/l	aquatic invertebrates	21 d
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	ErC50	45.6 µg/l	algae	120 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 3082
IMDG-Code	UN 3082
ICAO-TI	UN 3082

14.2 UN proper shipping name

DOT	Environmentally hazardous substance, liquid, n.o.s.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.
Technical name (hazardous ingredients)	Zinc oxide, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)

14.3 Transport hazard class(es)

DOT	9
IMDG-Code	9
ICAO-TI	9

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	Zinc oxide, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

DRYLOK Extreme Basement & Masonry Waterproofer (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN3082, Environmentally hazardous substance, liquid, n.o.s., (Zinc oxide, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate), solution), 9, III
Reportable quantity (RQ)	181,488 lbs (82,396 kg) (ammonia) (Ammonia, aqueous solution)
Danger label(s)	9, fish and tree
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	8, 146, 173, 335, IB3, T4, TP1, TP29
ERG No	171

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	yes (hazardous to the aquatic environment) (Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate))
Danger label(s)	9, fish and tree
Special provisions (SP)	274, 335, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-F
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	9, fish and tree
Special provisions (SP)	A97, A158, A197, A215
Excepted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
Aluminium oxide	1344-28-1	fibrous forms	1986-12-31

Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
2-methylpropane	75-28-5	Flammable substance	f	10000

Legend

f Flammable gas.

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Titanium dioxide	13463-67-7		IARC Carcinogens - 2B Prop 65
Diethylene glycol monomethyl ether (DM)			CA TACs
Quartz (SiO ₂)	14808-60-7		IARC Carcinogens - 1
2-methylpropane	75-28-5		EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Quartz (SiO ₂)		1095			1.0 %
Aluminium oxide	1344-28-1				1.0 %
Diethylene glycol monomethyl ether (DM)		1022			1.0 %
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)		1039			1.0 %

DRYLOK Extreme Basement & Masonry Waterproofer (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Quartz (SiO ₂)		A, *	
Titanium dioxide	13463-67-7	A	

Legend

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Quartz (SiO ₂)	14808-60-7		CA
Titanium dioxide	13463-67-7		
Aluminium oxide	1344-28-1		
Diethylene glycol monomethyl ether (DM)			
2-methylpropane	75-28-5		F4
Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)			

Legend

- CA Carcinogenic
F4 Flammable - Fourth Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
TITANIUM OXIDE (TiO ₂)	13463-67-7	
ALUMINUM OXIDE (Al ₂ O ₃)	1344-28-1	E
ETHANOL, 2-(2-METHOXYETHOXY)-	111-77-3	
ZINC	7440-66-6	*, E

Legend

- * Any compound of this substance is also an environmental hazard
E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Quartz (SiO ₂)	14808-60-7	T
Titanium dioxide	13463-67-7	T
Aluminium oxide	1344-28-1	T
2-methylpropane	106-97-8	T, F

Legend

- F Flammability (NFPA®)
T Toxicity (ACGIH®)

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
silica, crystalline		airborne particles of respirable size	cancer
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer
formaldehyde	50-00-0	gas	cancer
ethylene oxide	75-21-8		cancer
ethylene oxide	75-21-8		female
ethylene oxide	75-21-8		developmental, male
vinylidene chloride (1,1-dichloroethene)	75-35-4		cancer
acrylonitrile	107-13-1		cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.2	Technical name (hazardous ingredients): Ethoxylated Alcohols, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	Technical name (hazardous ingredients): Zinc oxide, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	yes
14.5	Environmentally hazardous substance (aquatic environment): Ethoxylated Alcohols, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	Environmentally hazardous substance (aquatic environment): Zinc oxide, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate)	yes

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	Particulars in the shipper's declaration: UN3082, Environmentally hazardous substance, liquid, n.o.s., (Ethoxylated Alcohols, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate), solution), 9, III	Particulars in the shipper's declaration: UN3082, Environmentally hazardous substance, liquid, n.o.s., (Zinc oxide, Zinc(2+) bis(2-sulfanylidene-1,2-dihydropyridin-1-olate), solution), 9, III	yes
15.1		Proposition 65 List of chemicals: change in the listing (table)	yes

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

DRYLOK Extreme Basement & Masonry Waterproofing (White)

Version number: REV 7.0
Replaces version of: 2022-06-07 (REV 6)

Revision: 2022-06-22

End of safety data sheet