

# Safety Data Sheet

Revision Date: 11-30-2015  
Product Code: FC7500

## 1. IDENTIFICATION

<b>Product Name</b>	<b>FC URETHANE BASECOAT GRAY</b>
<b>Product Code</b>	FC7500
<b>Document ID</b>	GFC7500
<b>Revision Number</b>	2
<b>Prior Version Date</b>	06-05-2015
<b>Intended Use</b>	Industrial Maintenance Floor BaseCoat Urethane
<b>Restrictions On Use</b>	For Industrial Use Only
<b>Chemical Family</b>	Urethane Coating
<b>Chemical Manufacturer / Importer</b>	NEOGARD® - a Division of JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
<b>Emergency Telephone Number:</b>	ChemTrec Center 1-800-424-9300 <b>International:</b> 703-527-3887

## 2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### Hazard Pictograms



**GHS Classification**  
Respiratory Sensitisation Category 1A  
Skin Sensitisation Category 1A  
Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2  
Carcinogenicity Category 2  
Acute Toxicity - Inhalation Dust / Mist Category 3

**Signal Word** Danger

**Hazard Statements** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer.

### Precautionary Statements

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, fume, mist, vapours or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection.

**Response** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

# Safety Data Sheet

Revision Date: 11-30-2015

Product Code: FC7500

present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a POISON CENTER or physician. Take off contaminated clothing and wash before reuse.

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal**

Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards Not Otherwise Classified (HNOC)**

Not applicable

**Additional Information**

Not applicable

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
1,3 Dioxolan-2-one, 4 methyl-	108-32-7	3 - 7
Titanium dioxide	13463-67-7	1 - 5
ISOPHORONE DIISOCYANATE	4098-71-9	1 - 5
Molecular sieves, 5A	69912-79-4	1 - 5
Quartz (Silica-Crystalline)	14808-60-7	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST-AID MEASURES**

<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If breathing difficulty persists or occurs later, consult a physician and have MSDS available.
<b>Eye Contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>Skin Contact</b>	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Thoroughly wash or discard clothing and shoes before reuse.
<b>Ingestion</b>	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS.

<b>Most Important Acute Symptoms and Effects</b>	Not Available
<b>Most Important Delayed Symptoms and Effects</b>	Not Available
<b>Special treatment needed:</b>	No additional first aid information available

**5. FIRE-FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
<b>Unsuitable Extinguishing Media</b>	No data available
<b>Fire and/or Explosion Hazards</b>	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
<b>Hazardous Combustion Products</b>	Carbon dioxide, Carbon monoxide, Nitrogen containing gases,

# Safety Data Sheet

Revision Date: 11-30-2015  
Product Code: FC7500

## Special Protective Equipment and Precautions for Fire-Fighters

Hydrogen cyanide, Isocyanic Acid, Isocyanates  
Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. See MSDS sections III, XIII and XV for disposal considerations.

### Methods and Material for Containment and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal.

## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing.

### Conditions for Safe Storage Materials to Avoid/Chemical Incompatibility

Store in a cool dry place. Keep container(s) closed.  
Oxidizing agents

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Limestone	15 mg/m <sup>3</sup> (total dust); 5 mg/m <sup>3</sup> (respirable fraction)		
Titanium dioxide	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	
Isophorone Diisocyanate		0.005 ppm (TWA)	
Quartz (Silica-Crystalline)	see Table Z-3	0.05 mg/m <sup>3</sup> TWA (respirable fraction)	

### Appropriate Engineering Controls Respiratory Protection

Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure.

General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use. For poorly ventilated areas or during spray application use NIOSH approved supplied air respirator unless air monitoring demonstrates vapor/mist levels below applicable limits. When monomeric isocyanate concentrations are below 0.05 ppm (10 times the 8 hour TWA exposure limit), an appropriate combination organic vapor and particulate respirator (NIOSH approved) may be appropriate. An end-of-service-life Indicator (ESLI) or a change schedule is mandatory.

### Eye Protection

Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

# Safety Data Sheet

Revision Date: 11-30-2015  
Product Code: FC7500

<b>Skin Protection</b>	station available. Avoid all skin contact by covering as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
<b>General Hygiene Conditions</b>	As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	
Physical State	Liquid
Color	Grey
<b>Odor</b>	No data available
<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available
<b>Melting Point/Freezing Point (°F/°C)</b>	No data available / No data available
<b>Initial Boiling Point and Boiling Range</b>	
Low (°F)	No data available
High (°F)	468.0
<b>Flash Point (°F/°C)</b>	250 / 121
<b>Evaporation Rate</b>	0.01 (n-Butyl Acetate = 1.0)
<b>Flammability (solid, gas)</b>	No data available
<b>Upper Flammable/Explosive Limit</b>	21.0
<b>Lower Flammable/Explosive Limit</b>	4.7
<b>Vapor Pressure</b>	77°F 0.00 kPA
<b>Vapor Density</b>	3.50
<b>Relative Density</b>	1.231
<b>Solubility in Water</b>	Reacts slowly with water.
<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition Temperature</b>	No data available
<b>Decomposition Temperature:</b>	No data available
<b>Viscosity</b>	105 - 115 KU
<b>Volatiles, % by volume</b>	0.40
<b>Volatiles, % by weight</b>	0.25
<b>Volatile Organic Chemicals (g/L)</b>	
(Regulatory, Calculated)	3.03
(Actual, Calculated)	3.03
<b>Density</b>	10.17 - 10.37 lbs./Gal

## 10. STABILITY AND REACTIVITY

---

<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	No data available
<b>Conditions to Avoid</b>	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Contamination.
<b>Incompatible Materials</b>	Oxidizing agents
<b>Hazardous Decomposition Products</b>	Carbon dioxide, Carbon monoxide, Nitrogen containing gases, Hydrogen cyanide, Isocyanic Acid, Isocyanates

## 11. TOXICOLOGICAL INFORMATION

---

<b>Routes of Exposure</b>	Skin contact Eye contact Ingestion Inhalation
---------------------------	--

# Safety Data Sheet

Revision Date: 11-30-2015  
Product Code: FC7500

## Immediate (Acute) Health Effects by Route of Exposure

<b>Inhalation Irritation</b>	Harmful if inhaled. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Irritating to the nose, throat, and respiratory tract. Sensitizer! Avoid exposure. If sensitized, exposure below the published exposure limits (e.g. TLV or PEL) can result in respiratory irritation, shortness of breath and difficulty breathing. These asthma-type symptoms may develop immediately or be delayed up to several hours.
<b>Skin Contact</b>	Causes irritation with symptoms of reddening, itching and swelling. Sensitizer. Avoid exposure. If sensitized, repeated exposures will result in irritation, reddening, and rashes even for very low exposures. May cause allergic skin reaction.
<b>Eye Contact</b>	Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible.
<b>Ingestion Irritation</b>	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort.

## Long-Term (Chronic) Health Effects Carcinogenicity

<b>Inhalation</b>	Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals. Cancer hazard: Contains Crystalline Silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces or spray mists. Isocyanate vapors or mist at concentrations above the TLV can irritate the mucous membranes in the respiratory tract causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function. Exposure well above the TLV may lead to generally reversible bronchitis, bronchial spasm and pulmonary edema. Repeated overexposure causes sensitization in some individuals resulting in asthma-like symptoms on subsequent exposures below the TLV. Persons with preexisting bronchial hyperactivity can respond to concentrations below the TLV with similar symptoms as well as an asthma attack. Overexposure may cause lung damage.
<b>Skin Contact</b>	Prolonged contact may cause an allergic skin reaction.

## Product Toxicology Data

### Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Aliphatic Polyisocyanate Resin	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	
Limestone	Oral LD50 Rat 6450 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.00 mg/L
1,3 Dioxolan-2-one, 4 methyl-	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 3000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L
Isophorone Diisocyanate	Oral LD50 Rat 5490 mg/kg	Dermal LD50 Rabbit 4780 mg/kg	Inhalation LC50 (4h) Rat 0.03 mg/L
Molecular sieves, 5A	Oral LD50 Rat > 2000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Quartz	Oral LD50 Rat > 22,500 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L

# Safety Data Sheet

Revision Date: 11-30-2015  
Product Code: FC7500

## Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
Titanium dioxide	2B		
Quartz	1		1

## 12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available)	No data available
Mobility in soil	No data available

## 13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste	Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.
------------------------	---

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint, Not-Regulated

Marine Pollutant: No

## 15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

### Regulated Components

#### SARA EHS Chemicals

	CAS #	%
Isophorone diisocyanate	4098-71-9	1 - 5
Propylene oxide	75-56-9	< 1 ppm

#### CERCLA

Not applicable

#### SARA 313

Isophorone diisocyanate	4098-71-9	1 - 5
-------------------------	-----------	-------

#### SARA 311/312

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	N
Pressure:	N
Reactivity:	Y

### U. S. State Regulations:

#### California Prop 65 Chemicals

##### Cancer

	CAS #	%
Titanium dioxide	13463-67-7	1 - 5
Crystalline Silica	14808-60-7	0.1 - 1

# Safety Data Sheet

**Revision Date:** 11-30-2015  
**Product Code:** FC7500

Carbon Black	1333-86-4	0.01 - 0.1
Propylene oxide	75-56-9	< 1 ppm
<b>Reproductive</b>		
Not applicable		

## **Canadian Regulations:**

**CEPA DSL:** The components of this product ARE listed on the Canadian Domestic Substances List.

**WHMIS Hazard Class:** D2A

## **16. OTHER INFORMATION**

---

**Revision Date** 11-30-2015

**Disclaimer** This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.