

SAFETY DATA SHEET

ZINC CLAD® 4100 (Part B)
Hardener
B69V120

Section 1. Identification

Product identifier : ZINC CLAD® 4100 (Part B)
Hardener
Product code : B69V120
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Material uses : Paint or paint related material.
: Industrial use only.

Supplier's details : The Sherwin-Williams Company
101 W. Prospect Avenue
Cleveland, OH 44115

Imported by: VALSPAR PAINT (AUSTRALIA) PTY LTD
L3, 2 Burbank Place,
Norwest, NSW, 2153
wattyl@wattyl.com.au

Emergency telephone number (with hours of operation) : 1-216-566-2917 (US) / +(61)290372994 (AUS) (Available 24 hrs/ 7 days)

Section 2. Hazard(s) identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms :



Signal word :

DANGER

Hazard statements :

Flammable liquid and vapor.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Section 2. Hazard(s) identification

- Prevention** : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapor. Wash thoroughly after handling.
- Response** : IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- Storage** : Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
- Other hazards which do not result in classification** : None known.

Section 3. Composition and ingredient information

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

CAS number/other identifiers

Not available.

| Ingredient name | % (w/w) | CAS number |
|-----------------------|-----------|------------|
| Epoxy Polymer | 30 - 60% | 67924-34-9 |
| Methyl Ethyl Ketone | 10 - <30% | 78-93-3 |
| Methyl n-Amyl Ketone | 10 - <30% | 110-43-0 |
| Xylene, mixed isomers | 10 - <30% | 1330-20-7 |
| Ethylbenzene | <10% | 100-41-4 |
| trimethylbenzene | <10% | 25551-13-7 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Section 4. First aid measures

- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazchem code : •3Y

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Avoid release to the environment.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-----------------------|--|
| Methyl Ethyl Ketone | Safe Work Australia (Australia, 12/2019). STEL: 890 mg/m ³ 15 minutes. STEL: 300 ppm 15 minutes. TWA: 445 mg/m ³ 8 hours. TWA: 150 ppm 8 hours. |
| Methyl n-Amyl Ketone | Safe Work Australia (Australia, 12/2019). TWA: 233 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. |
| Xylene, mixed isomers | Safe Work Australia (Australia, 12/2019). STEL: 655 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 350 mg/m ³ 8 hours. TWA: 80 ppm 8 hours. |
| Ethylbenzene | Safe Work Australia (Australia, 12/2019). STEL: 543 mg/m ³ 15 minutes. STEL: 125 ppm 15 minutes. TWA: 434 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. |
| trimethylbenzene | Safe Work Australia (Australia, 12/2019). TWA: 123 mg/m ³ 8 hours. TWA: 25 ppm 8 hours. |

Biological limit values : There is no biological limit allocated.

Section 8. Exposure controls and personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point, initial boiling point, and boiling range** : 78°C (172.4°F)

Section 9. Physical and chemical properties

| | |
|---|--|
| Flash point | : Closed cup: 27°C (80.6°F) [Pensky-Martens Closed Cup] |
| Evaporation rate | : 5.6 (butyl acetate = 1) |
| Flammability | : Not available. |
| Lower and upper explosion limit/flammability limit | : Lower: 0.7% Upper: 10% |
| Vapor pressure | : 12.1 kPa (90.6 mm Hg) |
| Relative vapor density | : 2.48 [Air = 1] |
| Relative density | : 0.94 |
| Solubility | : Not available. |
| Partition coefficient: n-octanol/water | : Not applicable. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Kinematic (40°C (104°F)): <20.5 mm ² /s (<20.5 cSt) |
| Heat of combustion | : 19.821 kJ/g |

Section 10. Stability and reactivity

| | |
|---|--|
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|----------------------|---------|-------------|----------|
| Methyl Ethyl Ketone | LD50 Dermal | Rabbit | 6480 mg/kg | - |
| | LD50 Oral | Rat | 2737 mg/kg | - |
| Methyl n-Amyl Ketone Xylene, mixed isomers | LD50 Oral | Rat | 1600 mg/kg | - |
| | LC50 Inhalation Gas. | Rat | 6700 ppm | 4 hours |
| Ethylbenzene | LD50 Oral | Rat | 4300 mg/kg | - |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| trimethylbenzene | LD50 Oral | Rat | 3500 mg/kg | - |
| | LD50 Oral | Rat | 8970 mg/kg | - |

Irritation/Corrosion

Section 11. Toxicological information

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| Methyl Ethyl Ketone | Skin - Mild irritant | Rabbit | - | 24 hours 14 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
| Methyl n-Amyl Ketone | Skin - Mild irritant | Rabbit | - | 24 hours 14 mg | - |
| Xylene, mixed isomers | Eyes - Mild irritant | Rabbit | - | 87 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 5 mg | - |
| | Skin - Mild irritant | Rat | - | 8 hours 60 uL | - |
| Ethylbenzene | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 100 % | - |
| | Skin - Mild irritant | Rabbit | - | 500 mg | - |
| | | | | 24 hours 15 mg | - |
| trimethylbenzene | Eyes - Mild irritant | Rabbit | - | 24 hours 500 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|-----------------------|------------|-------------------|------------------------------|
| Methyl Ethyl Ketone | Category 3 | - | Narcotic effects |
| Methyl n-Amyl Ketone | Category 3 | - | Narcotic effects |
| Xylene, mixed isomers | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|-----------------------|------------|-------------------|----------------|
| Xylene, mixed isomers | Category 2 | - | - |
| Ethylbenzene | Category 2 | - | hearing organs |

Aspiration hazard

| Name | Result |
|-----------------------|--------------------------------|
| Xylene, mixed isomers | ASPIRATION HAZARD - Category 1 |
| Ethylbenzene | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Section 11. Toxicological information

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

| Route | ATE value |
|---------------------|---------------|
| Oral | 6984.37 mg/kg |
| Dermal | 9576.47 mg/kg |
| Inhalation (gases) | 58329.41 ppm |
| Inhalation (vapors) | 53.17 mg/l |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|--------------------------------------|-------------------------------------|----------|
| Methyl Ethyl Ketone | Acute EC50 >500000 µg/l Marine water | Algae - Skeletonema costatum | 96 hours |
| | Acute EC50 5091000 µg/l Fresh water | Daphnia - Daphnia magna - Larvae | 48 hours |
| Methyl n-Amyl Ketone Xylene, mixed isomers | Acute LC50 3220000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute LC50 131000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute LC50 8500 µg/l Marine water | Crustaceans - Palaemonetes pugio | 48 hours |
| Ethylbenzene | Acute LC50 13400 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute EC50 4900 µg/l Marine water | Algae - Skeletonema costatum | 72 hours |
| | Acute EC50 7700 µg/l Marine water | Algae - Skeletonema costatum | 96 hours |
| | Acute EC50 6.53 mg/l Marine water | Crustaceans - Artemia sp. - Nauplii | 48 hours |
| trimethylbenzene | Acute EC50 2.93 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 4200 µg/l Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 5600 µg/l Marine water | Crustaceans - Palaemonetes pugio | 48 hours |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Methyl Ethyl Ketone | - | - | Readily |
| Methyl n-Amyl Ketone | - | - | Readily |
| Xylene, mixed isomers | - | - | Readily |
| Ethylbenzene | - | - | Readily |

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-------------|-----------|
| Xylene, mixed isomers | - | 8.1 to 25.9 | low |

Mobility in soil





Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | ADG | ADR/RID | IMDG | IATA |
|-----------------------------------|--|--|---|--|
| UN number | UN1263 | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL |
| Transport hazard class(es) | 3  | 3  | 3  | 3  |
| Packing group | III | III | III | III |
| Environmental hazards | Not applicable. | Not applicable. | Not applicable. | Not applicable. |
| Additional information | Hazchem code •3Y | Tunnel code D/E | Emergency schedules F-E, S-E | Not applicable. |

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Agricultural and Veterinary Chemicals Code Act 1994

Not available.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Section 15. Regulatory information

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Any other relevant information

History

Date of printing : 18, June, 2022.

Date of issue/Date of revision : 18, June, 2022

Date of previous issue : 04, November, 2021

Version : 8

Key to abbreviations : ADG = Australian Dangerous Goods
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SUSMP = Standard Uniform Schedule of Medicine and Poisons
UN = United Nations

Procedure used to derive the classification

| Classification | Justification |
|--|-----------------------|
| FLAMMABLE LIQUIDS - Category 3 | On basis of test data |
| SKIN CORROSION/IRRITATION - Category 2 | Calculation method |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A | Calculation method |
| SKIN SENSITIZATION - Category 1 | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 | Calculation method |
| ASPIRATION HAZARD - Category 1 | Calculation method |

References : Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified

Section 16. Any other relevant information

by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

End of SDS